

| **SCR-F Series**



The SCR-F series of crash rails provide impact resistance with a continuous aluminum retainer or aluminum clips. For additional shock absorption, choose from three mounting options.

**Features**

- PVC-free Acrovyn®
- Flat edge that's impact resistant
- 3 profile sizes available

**Benefits**

- Shock absorbing; designed to take impact
- Covers easily replaced
- Multiple aesthetic and functional options available to meet any design requirement

**Applications**

- Corridors
- Elevator lobbies
- Lobbies
- Mail rooms
- Headwalls

**Building Segments**

- Healthcare
- Office & Mixed Use
- Retail
- Hospitality
- Senior Living
- Sports & Entertainment
- Aviation & Transportation

CRASH RAILS

**SCR-F Series**

**Product Details**

- .078" (1.98mm) thick Acrovyn® cover & end caps
- Acrovyn shadowgrain texture
- 90° & odd outside corners available
- Lengths up to 20' (6.1mm)
- Factory formed radius (not available with clip models)
- Regrind PETG mounting cushion

**Certifications**


- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 & G 21-96)
- Chemical resistant (per ASTM D 543)
- Impact resistant (per ASTM F 476-84)
- UL Class A/1 fire rated & labeled
- California 01350 Testing (VOC Emissions)
- Cradle-to-Cradle Certified™ Silver



**Finish Options**



**Mounting Options**



See all finish and mounting options online at [c-sgroup.com](http://c-sgroup.com).

**Warranty**

- Acrovyn Limited Lifetime Warranty

**Model Details**

Model	Profile	Mount	Wall Offset	Ramp Transition	Buy Online
SCR-40	4" (101.6mm)	Surface mounted continuous aluminum retainer	3/4" (19.1mm)	√	√
BCR-40	4" (101.6mm)	1/2" (12.7mm) bumper mounted continuous aluminum retainer	1 3/16" (30.2mm)	√	√
ECR-40	4" (101.6mm)	2 1/8" (54.0mm) mounting bracket continuous aluminum retainer	2 7/8" (73.0mm)	√	√
SCR-48	6" (152.4mm)	Surface mounted 1 1/2" (38.1mm) aluminum clips	1 1/4" (31.8mm)	√	√
SCR-48M	6" (152.4mm)	Surface mounted continuous aluminum retainer	1 1/4" (31.8mm)	√	√
BCR-48	6" (152.4mm)	1/2" (12.7mm) bumper mounted continuous aluminum retainer	1 3/4" (44.5mm)	√	√
ECR-48	6" (152.4mm)	2 1/8" (54.0mm) mounting bracket continuous aluminum retainer	3 7/16" (87.3mm)	√	√
SCR-64	8" (203.2mm)	Surface mounted 1 1/2" (38.1mm) aluminum clips	1 1/4" (31.8mm)	√	√
SCR-64M	8" (203.2mm)	Surface mounted continuous aluminum retainer	1 1/4" (31.8mm)	√	√
BCR-64	8" (203.2mm)	1/2" (12.7mm) bumper mounted continuous aluminum retainer	1 3/4" (44.5mm)	√	√
ECR-64	8" (203.2mm)	2 1/8" (54.0mm) mounting bracket continuous aluminum retainer	3 7/16" (87.3mm)	√	√