

| **SCR-R Series**



The SCR-R series of crash rails provide impact resistance with a continuous aluminum retainer or aluminum clips. Available in surface and bumper mounting options with a continuous cushion for additional shock absorption.

Features

- PVC-free Acrovyn®
- 2 profile sizes available
- Cover snaps over a continuous aluminum retainer or mounting clips
- Vertical accent reveal between end cap & cover available in select Acrovyn solid colors

Benefits

- Rounded edge offers a nice radius look and prevents dust collection
- Shock absorbing; designed to take impact
- Covers easily replaced

Applications

- Corridors
- Elevator lobbies
- Lobbies
- Mail rooms
- Headwalls

Building Segments

- Aviation & Transportation
- Healthcare
- Office & Mixed Use
- Retail
- Hospitality
- Senior Living
- Sports & Entertainment

CRASH RAILS

SCR-R Series

Product Details

- .078" (1.98mm) thick Acrovyn® cover & end caps
- Acrovyn shadowgrain texture
- 90° outside corners
- Available up to 20' (6.1m) lengths
- Factory formed radius (not available with clip models)

Certifications


- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 & G 21-96)
- Chemical resistant (per ASTM D 543)
- Impact resistant (per ASTM F 476-84)
- UL Class A/1 fire rated & labeled
- California 01350 Testing (VOC Emissions)
- Cradle-to-Cradle Certified™ Silver



Finish Options



Mounting Options



See all finish and mounting options online at c-sgroup.com.

Warranty

- Acrovyn Limited Lifetime Warranty

Model Details

Model	Profile	Mount	Wall Offset	Ramp Transition	Buy Online
SCR-50	5" (127mm)	1" (25.4mm) aluminum clips	1 1/16" (26.9mm)	✓	✓
SCR-50M	5" (127mm)	Aluminum retainer	1 1/16" (26.9mm)	✓	✓
BCR-50	5" (127mm)	1/2" (12.7mm) mounting cushion	1 1/2" (38.1mm)	✓	✓
SCR-80	8" (203.2mm)	1 1/2" (38.1mm) mounting clips	1 3/8" (34.9mm)	✓	✓
SCR-80M	8" (203.2mm)	Aluminum retainer	1 3/8" (34.9mm)	✓	✓
BCR-80	8" (203.2mm)	1/2" (12.7mm) mounting cushion	1 13/16" (46.0mm)	✓	✓